

**band  
saw**

**300 W  
245 mm**

**RYOBI**

**RBS-3080**



Non contractual document and photos.

Circle cutting attachment for cutting to 250 mm radius

Right or left rip fence: especially advantageous for 45° cuts

Polished cast iron table tilts up to 45°

35 /100 mm dust extraction port

Long life powerful asynchronous motor develops a high torque

Band tension adjustment knob

Band alignment knob

The long life time precision 3-roller guide with tungsten carbide thrust and bearings provides excellent guidance to the saw blade

Upper and lower die cast aluminium wheels are rubber coated to prevent band from slipping out. Lower wheel is continuously cleaned from dust by a fixed brush.

Wheels diameter : 250 mm

Wheels covers with anti-vibrations and dust rubber seal

Strongly built work stand with profiled steel base **OPTIONAL** workstand  
ref : RWT-250

#### technical specifications

input power	300 W
blade speed	900 m/min
table size	343 x 362 mm
working height	980 mm avec RWT 250
depth of cut	90 mm max
saw table tilt to	45° max
throat capacity	245 mm
saw band size	1700 x 10 x 0,35 mm
machine dimensions	475 x 325 x 850 mm
weight	35 kg

#### standard accessories

Circle cutting attachment (004512)  
Band 1700 x 10 x 0,35 mm  
(004515)  
Rip fence (004510)

#### optional accessories

Workstand RWT-250  
Replacement band  
Bevel cut fence (004511)  
Wheel set RWS-315  
Roller stand

#### gencod

4960673 103209